Printed Pages: 02	Sub Code: RCE401										
Paper Id: 100431	Roll No.										

# B.TECH (SEM IV) THEORY EXAMINATION 2017-18 HYDRAULICS & HYDRAULIC MACHINES

Time: 3 Hours Total Marks: 70

**Note:** Attempt all Sections. If require any missing data; then choose suitably.

#### **SECTION A**

## 1. Attempt all questions in brief.

 $2 \times 7 = 14$ 

- a. Define Different types of flow.
- b. Determine the maximum discharge through a rectangular open channel of area 8m³ with a bed slope of 1/2000. Assume manning's constant 0.022.
- c. Define the velocity contour's in open channel flow.
- d. What is the Back Water Curve?
- e. Write the types of Surge.
- f. What assumptions will take in Velocity Triangles?
- g. Write the main Parts of Kaplan Turbines.

#### **SECTION B**

# 2. Attempt any three of the following:

 $7 \times 3 = 21$ 

- a. Uniform flow occurs at a depth of 1.5 m in a long rectangular channel 3 m wide and laid to a slope of 0.0009. If manning's n=0.015. Calculate (a) Maximum height of hump on the floor to produce critical depth (b) The width of contraction which will produce critical depth without increasing the upstream depth of flow.
- b. In an open channel, the Froude number F remains constant at all depths. if the specific energy E is constant Show that

$$\frac{T}{B} = \left(\frac{E}{E - h}\right)^{\left(\frac{1 + F^2}{2}\right)}$$

- c. Prove that Hydraulically most efficient trapezoidal section is half of regular Hexagon.
- d. Integrate the differential equation of G.V.F. for a Horizontal Channel to get the Profile equation as

$$x = \frac{h_c}{S_c} \left[ \frac{\left(\frac{h}{h_c}\right)^{N-M+1}}{N-M+1} - \frac{\left(\frac{h}{h_c}\right)^{N+1}}{N+1} \right] + constt.$$

e. What is NPHS of centrifugal Pump? How it is related to cavitation in Pump?

## 3. Attempt any *one* part of the following:

 $7 \times 1 = 7$ 

- (a) An open channel to be made of concrete is to be designed to carry 1.5m3/s at a slope of 0.00085. Find the most efficient cross section for (a) Rectangular section (b) Trapezoidal section (c) Semicircular section
- (b) Define the following with formula (a) Kinetic Energy Correction factor (b) Momentum correction factor

#### 4. Attempt any *one* part of the following:

 $7 \times 1 = 7$ 

- (a) Using Basic differential equation of G.V.F. show that dh/dx is positive for S<sub>1</sub>, M<sub>3</sub> and S<sub>3</sub> Profiles.
- (b) How you will define Transitions between Sub Critical Flow And Super Critical Flow? Also draw the Diagram.

#### 5. Attempt any *one* part of the following:

 $7 \times 1 = 7$ 

- (a) A rectangular channel carrying a super critical stream is to be provided with a hydraulic jump type of energy dissipater. It is desired to have an energy loss of 5 m in hydraulic jump when inlet Froude's number is 8.5. What are the segment depths of this jump?
- (b) Derive the relation between velocity and depths of flow where positive surges moving upward.

## 6. Attempt any *one* part of the following:

 $7 \times 1 = 7$ 

- (a) In order to predict the performance of a large centrifugal pump, a scale model of one sixth size was made with following specifications. Power = 25 KW,  $H_{man}$  =7 mtr, N=1000rpm. If prototype works against 22m. Calculate its working speed, the power required to derive it and the ratio of flow rates handled by to pups.
- (b) Define cavitation. And what precautions taken against Cavitation?

## 7. Attempt any *one* part of the following:

 $7 \times 1 = 7$ 

- (a) A Pelton wheel is to be designed for the following specification. Shaft power =11722 KW, Head =380 mtr, speed =750rpm,  $\eta_0$  = 86% Jet diameter (d) not to exceed one-sixth of wheel diameter. Determine (i) The wheel Diameter (ii) Number of jet required (iii) Diameter of jet Take velocity ratio  $K_{v1}$ =0.985 and speed Ratio  $K_{u1}$ =0.45
- (b) Define different types of efficiency of Hydraulic turbines.